



Nauchny proezd, 20
117246, Russia, Moscow



+7 963 612-3113
+7 926 059-5020



info@movicomreelers.ru



<http://movicomreelers.ru>



MICROPHONE AND LOUDSPEAKER REELERS

Although Movicom makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Movicom provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Movicom be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Movicom has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Movicom products are subject to Movicom's standard terms and conditions of sale.

MICROPHONE REELER

Cable length	16 or 25 meters
Cable type	Microphone StarQuad (four insulated twisted conductors in a common braided copper shield)
Cable diameter	3,4 mm
Speed	controlled, up to 0,5 m/sec
Maximum allowable load weight	Up to 2 kg
Positioning accuracy	+/- 1 cm
Microphone connector type	XLR 3 pin, LEMO optionally
Power supply	110-220 V AC, 24 or 48 V DC optionally. 250 W peak power
Control	In operational mode – from control server. In service mode – local pushbuttons
Dimensions	405 x 505 x 140 mm
Weight	25 kg

Microphone and loudspeaker reelers provide precise vertical positioning of microphones and active loudspeakers in theaters, auditoriums, studios, concert and conference halls and in other situations that require quick vertical microphone or loudspeaker repositioning. Possible applications include sound recording, TV productions and microphones and loudspeakers repositioning as a part of dynamically-reconfigurable acoustics system.

The microphone reeler is available in two modifications: with 16 m and 25 m cable lengths. Other cable lengths are available on request. A professional Starquad microphone cable provides a very high EMI and RFI noise immunity and makes it possible to use the microphone reelers in the most unfavorable electromagnetic conditions, for example in proximity of lighting equipment. Cable outer diameter may be specified at the point of order.

For safety purpose, user can limit the maximum deployment length of the cable that corresponds to the lowest operational position of a microphone.

Standard mounting options include grips for fixing the reeler on a 50-60 mm pipe and fixtures to install the reeler on a stage grid. Other fixtures are available on request.



CONTROL SYSTEM

The reelers are controlled by a special control server via Ethernet network. One control server may control up to 100 reelers. An additional portable controller (a PC and / or a tablet) may connect to the server to allow convenient on-site system operation.

The control system includes emergency stop functions and optional backup manual control buttons to control the devices in case of communication failure.

Integration with third-party systems (for example, dynamically configurable acoustics systems) is available on request.

THE CONTROL SOFTWARE PROVIDES THE FOLLOWING FUNCTIONS:

- Speed and position control of each reeler separately.
- Speed and position control of a group of reelers
- Quick-select groups (virtually unlimited number of reeler groups may be created).
- Position presets for individual reelers and groups.
- Groups of presets for different shows.
- Individual names for every reeler, preset and group.
- Using an image (e.g. a floorplan) as a background for reeler choice interface.
- Height limit settings.
- Real-time status data for each reeler.

LOUDSPEAKER REELER

Cable length	16 or 25 meters
Cable type	Special: • 22 AWG stranded conductors, shielded for audio • 18 AWG stranded conductors for power • Kevlar reinforcement
Cable diameter	6,5 mm
Speed	controlled, up to 0,5 m/sec
Maximum allowable load weight	Up to 10 kg
Positioning accuracy	+/- 1 cm
Microphone connector type	XLR 5 pin
Power supply	110-220 V AC, 24 or 48 V DC optionally. 350 W peak power
Control	In operational mode – from control server. In service mode – local pushbuttons
Dimensions	735 x 590 x 185 mm
Weight	45 kg



The loudspeaker reeler is similar by design to the microphone reeler and provides the same control functions. However, it works with a specially-designed cable combining a shielded conductor pair (22 AWG) for audio signal, an unshielded power feed pair (18 AWG) and a Kevlar core to ensure cable integrity. The maximum load of the cable is 10 kg. The use of the cable as a carrier with this load conforms all major safety standards.

TABLET APPLICATION

