

Technical specifications

Continuous power: 4 000 W Maximum power (0.5s): 8 000 W Battery capacity: 5 100 Wh Output voltage: 230Vac - 50Hz

AC Output: 1 Type F – 16A (3500 W max) AC Inputs: 1 Power Twist NCA3 - 20A 1 prise Anderson 50 A (PV 5000 W) **Recharge time (16A):** < 3h (90%) Operating time at 500 W: > 9 h Operating time at 1000 W:>4 h Operating time at 2000 W:> 2 h **Battery life time:** 2000 Cycle (8 years)

Weight: 55kg

Dimensions: 42x46x62(h)cm

Standard: IP22 IK07

Humidity (does not include mist): 5 – 95%

Noise level: 20dB(a)

Noise level when charging: 30dB(a) CE-certified: DIRECTIVE BT (2014/35/UE) et

CEM (2014/30/UE)

Operating temperature: 0°C / 40°C

With the battery warning system: - 10°C/

40°C

Options

Extension of warrantee Contract maintenance Miscellaneaous cables

Rain cover

InfiniT Solution: transfer automatically the power from one powerbank to another

without blackout

Mobile solar panel range: EKLA

A large amount of energy in a very compact design, Bobine will be your best partner to power all your electrical equipment everywhere, without any noise or gas emissions. This light, portable and tough solution is very easy to handle. The strongest materials have been choosen to ensure a long-life cycle and easy repairs. With a battery capacity up to 10 hours and its fastcharging system, you can easily manage your power supplies.

Li-Ion Battery

Maintenance-free Noiseless No gas emission

Smart RMS High energy density Off-road

Powerful Guaranteed Movable Solar recharge No smell **CE-certified** Fast charge



MADE IN FRANCE